


# CONTRACT PROOFING PAPER 260G



## Description

PerfectProof Contract Proofing Paper is a **heavyweight semi-matte** paper for High-End proofing applications.

Fogra certified (substrate & systems), this paper guarantees you the perfect color gamut reproduction of any local or international press standards. Regardless you want to mimic **GRACoL**, **SWOP** or **ISO12647:2004** (Fogra), it will help you to easily **certify your jobs**. The Contract Proofing Paper has been specially developed to reduce metamerism and matting effects. It is available in sheets and in rolls: rolls are mounted on 3" core to prevent your proofs from curling.

## APPLICATION GUIDELINES

Proofing commercial (Offset,Cromalin) for certified proofs

## PRINTER COMPATIBILITY

	Stylus Photo (1200,1270,1280,1290,1520,2000p,2100/2200,R2400)
<b>Epson</b>	Stylus Pro (3000,4000,4400,4800,5000,5500,7000,7400,7500,7600,7800,9000,9400,9500,9600,9800,10000,10000CF,10600)
<b>Hewlett Packard</b>	DesignJet (10,20,30,50,90,100,120,130,800,1050,1055,2x00,3x00,3500,4000,5000,5500)
<b>Canon</b>	i9100,s9000,BJ (C8500,W7000S,W9000), imagePROGRAF (W2200,W6200,W6400,W7200,W7250,W8200,W8400)
<b>Agfa</b>	Sherpa (2,24,43,54,62),Grand Sherpa (50,64,87)
<b>Roland</b>	HifiJet Pro (FJ-400/500/600) & Pro II(FJ-540),CammJet Pro (CJ-400/500) & Pro II(CJ-540)
<b>Mutoh</b>	RJ-800,RJ-4100,RJ-6100,Rockhopper,Falcon2 RJ8000

## AVAILABILITY

<b>30m (98.4ft) rolls:</b>	13"(0.33m)	17"(0.43m)	24"(0.61m)	44"(1.12m)
<b>Part:</b>	194136	194176	194096	194046
<b>50 sheets:</b>	A3+(330x483mm)	A1 (594x841mm)		
<b>Part:</b>	194006	194336		

## PHYSICAL PROPERTIES

<b>Finish:</b>	Microporous Semi-Matte finish
<b>Ink Compatibility:</b>	Dye, Pigment and UltraChrome inks (K2 & K3)
<b>Drying Time:</b>	Instant
<b>Resolution:</b>	Recommended: max 2880 dpi
<b>Brightness:</b>	92%
<b>Opacity:</b>	>96%
<b>Gloss 75°:</b>	47%
<b>Tint (Lab):</b>	94.6,-0.6,-3.7 (Fogra certified on ISO12647-2 (Pt1,2&3) ISO12647-4 (S1,S2,S3&S4))
<b>Production Delta E:</b>	< 0.9

**Lamination:** Hot: Yes / Cold: Yes

**Storage:** After printing, unused material should be stored in its original packaging. Protect it from direct sunlight and moisture. Between 18 and 23c° at 50% relative humidity.